

MEDIUM VOLTAGE FEEDER SECTION

- Free standing, single high compact feeder capacitor. Feeder controller to comply with NEMA1CS2-324.
- Fault Make, Load break visible blade disconnect switch with automatic grounding arm.
- Grounded metal isolation between LV and Medium Voltage Compartments.
- Maintenance free Joslyn Clark Vacuum Contactors.
- Suitably rated current limiting power fuses with striker pins and 3 phase trip bar.
- C.P.T. provided with 2 primary and 1 secondary fuses, 120V secondary.



- Transformer ratings assume 100% continuous rating for operation at overload ratings Consult Factory
- For latched contactors change "MVF" to "MVFL" add 1281 to list price & specify trip coil voltage.

Ampere Rating	KVA Ratings	K R	
2300V	VACUUM STARTERS With Fused Load Break Disconnect		
200 AMP	750	550	MVF18TA32A25-T236
400 AMP	1500	1125	MVF18TA34A25-T236
600 AMP	2500	1650	MVF18TA36A25-T236
800 AMP	2750	2200	MVF18TA38A25-T236
1200 AMP	4100	2750	MVF18TA312A25-T236

Ampere Rating	KVA Ratings	KVAR Rating	Catalog No.
4160V	VACUUM STARTERS With Fused Load Break Disconnect		
200 AMP	1500	1050	MVF18TA32A25-T486
400 AMP	3000	2250	MVF18TA34A25-T486
600 AMP	4250	3375	MVF18TA36A25-T486
800 AMP	5250	4500	MVF18TA38A25-T486
1200 AMP	7000	5625	MVF18TA312A25-T486

Ampere Rating	KVA Ratings	KVAR Rating	Catalog No.
7200V	VACUUM STARTERS With Fused Load Break Disconnect		
200 AMP	2000	1500	MVF18TA32A25-T666
400 AMP	4000	3000	MVF18TA34A25-T666
600 AMP	6000	4500	MVF18TA36A25-T666
800 AMP	7500	5000	MVF18TA38A25-T666